



Material: S 235 JR

Vse dimenzije so v milimetrih./All dimensions are in millimetres.

Bat Piston	UC Ø	FC Ø	FB Ø	BC Ø e8	C Ø	L *	NF *	VD	P **	Šifra Code
25	85	65	9	45	34	14	8	3	-	34527
32	95	75	9	55	41	16	10	3	-	34528
40	104	85	11	65	49	20	14	3	-	34518
50	118	95	11	75	59	23	17	3	-	34519
63	138	115	13	90	74	28	22	3	5/30°	34520
70	158	125	13	100	84	31	25	3	5/30°	34529
80	178	145	17	115	94	33	27	3	5/30°	34521
90	188	155	17	125	104	33	27	3	5/30°	34530
100	205	170	17	140	114	38	32	3	6/30°	34522
110	225	190	17	160	129	38	32	3	6/30°	34531
125	245	205	21	165	143	41	35	3	6/30°	34523
140	300	250	26	200	163	41	35	3	8/30°	34509
160	335	275	30	225	187	46	40	3	8/30°	34532
180	380	310	30	255	217	56	50	3	8/30°	34525
200	410	345	33	285	242	56	50	3	8/30°	34524
250	470	405	33	345	296	66	60	3	10/30°	34533

* Prirobnico je potrebno po varjenju postružiti, da se zagotovi ustrezna pravokotnost prirobnice s cevjo, zato imajo mere L, NF in BC dodatek za struženje, ki ni všteti v tabeli.

* Once welding is finished, flange needs to get planed to assure required perpendicularity of the flange in regard to the tube, that is why dimensions L, NF and BC are augmented by planing addition, not given in the table.

** Prirobnico se privariva z obeh strani./Flange is to be welded from both sides.